



MATERIAL SAFETY DATA SHEET

Page 1 of 5

Sika Armatec 110 - Part C

HMIS

HEALTH	*2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 03/03/2005

Product Name: Sika Armatec 110 - Part C
Chemical Family: Cementitious Mortar
Chemical Formula: RMF-1609
MSDS Number: 3485
Product Code: 018219N

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CEMENT, PORTLAND	65997-15-1	30 - 35
SILICA, QUARTZ	14808-60-7	60 - 65
SODIUM NITRITE	7632-00-0	1 - 5

3. Hazards Identification

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause respiratory tract irritation. Breathing dust may cause nose, throat or lung irritation. Respirable crystalline silica can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive.

Sika Armatec 110 - Part C

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: N/A °F

Autoignition Point: N/A °F

Fire And Explosion Hazards

None Known

Extinguishing Media

Use the appropriate extinguishing media for the surrounding fire.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Using appropriate personal protective equipment (PPE), shovel material into waste containers taking care to minimize dust. Dampen if necessary to control dust. Vacuum clean dust with equipment fitted with High Efficiency Particulate Air (HEPA) filters.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure. Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Sika Armatec 110 - Part C

8. Exposure Controls/Personal Protection - Continued

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

CEMENT, PORTLAND

ACGIH TLV-TWA - 10 mg/m³

OSHA PEL -TWA - 15 mg/m³ (total dust)

OSHA PEL - TWA - 5 mg/m³ (respirable dust)

SILICA, QUARTZ

ACGIH TLV-TWA 0.1 mg/m³ (Notice of Intended Change)

ACGIH TLV-TWA 0.05 mg/m³ (Proposed)

OSHA PEL-TWA 30/%SiO₂+2 mg/m³

OSHA PEL-TWA 10/%SiO₂+2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

9. Physical And Chemical Properties

Appearance

Solid/Sand

Odor

Cement

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/A °F

Specific Gravity: 2.70

Vapor Pressure: N/A

Vapor Density: N/A

pH Factor: 11

Solubility: N/A

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

None Known

Incompatible Materials

None Known

Hazardous Decomposition Products

None Known

11. Toxicological Information

Ingredient(s) - Carcinogenicity

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

Sika Armatec 110 - Part C

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

SARA Title III - Section 313 Supplier Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

SODIUM NITRITE (7632-00-0) 1 - 5 %

This information must be included on all MSDSs that are copied and distributed for this material.

Ingredient(s) - U.S. Regulatory Information

SODIUM NITRITE
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Ingredient(s) - State Regulations

SILICA, QUARTZ
New Jersey - Workplace Hazard
Pennsylvania - Workplace Hazard
California - Proposition 65
Massachusetts - Hazardous Substance
SODIUM NITRITE
New Jersey - Workplace Hazard
New Jersey - Environmental Hazard
Pennsylvania - Workplace Hazard
Pennsylvania - Environmental Hazard
New York City - Hazardous Substance

16. Other Information

HMIS Rating

Health: *2

Fire: 0

Reactivity: 0

PPE: C

MATERIAL SAFETY DATA SHEET

Sika Armatec 110 - Part C

16. Other Information - Continued

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION